

Advance GTVA123501FA

Thermally-Enhanced High Power RF GaN on SiC HEMT 350 W, 50 V, 1200 – 1400 MHz

Description

The GTVA123501FA is a 350-watt GaN on SiC high electron mobility transistor (HEMT) for use in the 1200 to 1400 MHz frequency band. It features input matching, high efficiency, and a thermally-enhanced surface-mount package with earless flange.

Features

- GaN on SiC HEMT technology
- Broadband internal input matching
- Pb-free and RoHS compliant

Advance Specification Data Sheets describe products that are being considered by Wolfspeed for development and market introduction. The target performance shown in Advance Specifications is not final and should not be used for any design activity. Please contact Wolfspeed about the future availability of these products.



GTVA123501FA
Package H-37265J-2

Target RF Characteristics

Typical RF Performance (tested in Wolfspeed test fixture)

$V_{DD} = 50\text{ V}$, $I_{DQ} = 300\text{ mA}$, $P_{OUT} = 350\text{ W}$, $f = 1200 - 1400\text{ MHz}$, Pulse Width = 300 μs , 10% duty cycle

Characteristic	Symbol	Min	Typ	Max	Unit
Linear Gain	G_{ps}	—	18	—	dB
Drain Efficiency	η_D	—	71	—	%

All published data at $T_{CASE} = 25^\circ\text{C}$ unless otherwise indicated

ESD: Electrostatic discharge sensitive device—observe handling precautions!

DC Characteristics

Characteristic	Conditions	Symbol	Min	Typ	Max	Unit
Drain-source Breakdown Voltage	$V_{GS} = -8\text{ V}$, $I_D = 10\text{ mA}$	$V_{(BR)DSS}$	150	—	—	V
Gate Threshold Voltage	$V_{DS} = 10\text{ V}$, $I_D = 42\text{ mA}$	$V_{GS(th)}$	-6	-3	-2.2	V

Recommended Operating Conditions

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Drain Operating Voltage		V_{DD}	0	—	55	V
Gate Quiescent Voltage	$V_{DS} = 50\text{ V}$, $I_D = 100\text{ mA}$	$V_{GS(Q)}$	—	-3.2	—	V

Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Drain-source Voltage	V_{DSS}	125	V
Gate-source Voltage	V_{GS}	-10 to +2	V
Gate Current	I_G	38	mA
Drain Current	I_D	5	A
Junction Temperature	T_J	225	°C
Storage Temperature Range	T_{STG}	-65 to +150	°C

Operation above the maximum values listed here may cause permanent damage. Maximum ratings are absolute ratings; exceeding only one of these values may cause irreversible damage to the component. Exposure to absolute maximum rating conditions for extended periods may affect device reliability. For reliable continuous operation, the device should be operated within the operating voltage range (V_{DD}) specified above.


Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction to Case ($f = 1.3\text{ GHz}$, $V_{DS} = 50\text{ V}$, $I_{DQ} = 100\text{ mA}$, $T_F = 70\text{ °C}$, $P_{OUT} = 300\text{ W}$, Pulse Width = 300 μs , 10% duty cycle)	$R_{\theta JC}$	0.17	°C/W

Ordering Information


Type and Version	Order Code	Package	Shipping
GTVA123501FA V1 R0	TBD	H-37265J-2, earless flange	Tape & Reel, 50 pcs
GTVA123501FA V1 R2	TBD	H-37265J-2, earless flange	Tape & Reel, 250 pcs

Pinout Diagram (top view)



Lead connections for GTVA123501FA

Package Outline Specifications



Revision History

Revision	Date	Data Sheet Type	Page	Subjects (major changes since last revision)
01	2016-05-23	Advance	All	Data Sheet reflects advance specification for product development
02	2016-05-08	Advance	All	Converted to Wolfspeed Data Sheet, updated DC and thermal characteristics

For more information, please contact:

4600 Silicon Drive
 Durham, North Carolina, USA 27703
www.wolfspeed.com/RF

Sales Contact
RFSales@wolfspeed.com

RF Product Marketing Contact
RFMarketing@wolfspeed.com
 919.407.7816

Notes

Disclaimer

Specifications are subject to change without notice. Cree, Inc. believes the information contained within this data sheet to be accurate and reliable. However, no responsibility is assumed by Cree for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Cree. Cree makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. "Typical" parameters are the average values expected by Cree in large quantities and are provided for information purposes only. These values can and do vary in different applications and actual performance can vary over time. All operating parameters should be validated by customer's technical experts for each application. Cree products are not designed, intended or authorized for use as components in applications intended for surgical implant into the body or to support or sustain life, in applications in which the failure of the Cree product could result in personal injury or death or in applications for planning, construction, maintenance or direct operation of a nuclear facility.