


PXFE211507FC


Thermally-Enhanced High Power RF LDMOS FET 170 W, 28 V, 2110 – 2170 MHz

Description

The PXFE211507FC is a 170-watt LDMOS FET intended for use in multi-standard cellular power amplifier applications in the 2110 to 2170 MHz frequency band. Features include input and output matching, high gain and thermally-enhanced package with earless flange. Manufactured with Wolfspeed's advanced LDMOS process, this device provides excellent thermal performance and superior reliability



PXFE211507FC
Package H-37248G-4/2



Features

- Broadband internal input and output matching
- Typical Pulsed CW performance, 2140 MHz, 28 V, single side, 16 μs , 10% duty cycle, class AB test
 - Output power at $P_{1dB} = 172\text{ W}$
 - Output power at $P_{3dB} = 208\text{ W}$
 - Efficiency at $P_{3dB} = 64.4\%$
 - Gain = 20.3 dB
- Capable of handling 10:1 VSWR @ 28 V, 120 W (CW) output power
- Human Body Model Class 2 (per ANSI/ESDA/JEDEC JS-001)
- Integrated ESD protection
- Low thermal resistance
- Pb-free and RoHS compliant

Single-carrier WCDMA Specifications (tested in Wolfspeed test fixture)

$V_{DD} = 28\text{ V}$, $I_{DQ} = 900\text{ mA}$, $P_{OUT} = 50\text{ W}$ avg, $f = 2170\text{ MHz}$, 3GPP signal, channel bandwidth = 3.84 MHz, peak/average = 10 dB @ 0.01% CCDF

| Characteristic | Symbol | Min | Typ | Max | Unit |
|---|----------|-----|-----|-------|------|
| Gain | G_{ps} | 17 | 18 | — | dB |
| Drain Efficiency | η_D | 33 | 35 | — | % |
| Adjacent Channel Power Ratio | ACPR | — | -29 | -27.5 | dBc |
| Output PAR at 0.01% probability on CCDF | OPAR | 5.5 | 6 | — | dB |

All published data at $T_{CASE} = 25^\circ\text{C}$ unless otherwise indicated

ESD: Electrostatic discharge sensitive device—observe handling precautions!



DC Characteristics

| Characteristic | Conditions | Symbol | Min | Typ | Max | Unit |
|--------------------------------|--|---------------|-----|------|-----|---------------|
| Drain-Source Breakdown Voltage | $V_{GS} = 0\text{ V}, I_{DS} = 10\text{ mA}$ | $V_{(BR)DSS}$ | 65 | — | — | V |
| Drain Leakage Current | $V_{DS} = 28\text{ V}, V_{GS} = 0\text{ V}$ | I_{DSS} | — | — | 1 | μA |
| | $V_{DS} = 60\text{ V}, V_{GS} = 0\text{ V}$ | I_{DSS} | — | — | 10 | μA |
| Gate Leakage Current | $V_{GS} = 10\text{ V}, V_{DS} = 0\text{ V}$ | I_{GSS} | — | — | 1 | μA |
| On-State Resistance | $V_{GS} = 10\text{ V}, V_{DS} = 0.1\text{ V}$ | $R_{DS(on)}$ | — | 0.03 | — | Ω |
| Operating Gate Voltage | $V_{DS} = 28\text{ V}, I_{DQ} = 900\text{ mA}$ | V_{GS} | 2.7 | 3.0 | 3.3 | V |

Maximum Ratings

| Parameter | Symbol | Value | Unit |
|---------------------------|-----------|-------------|--------------------|
| Drain-Source Voltage | V_{DSS} | 65 | V |
| Gate-Source Voltage | V_{GS} | -6 to +10 | V |
| Operating Voltage | V_{DD} | 0 to +32 | V |
| Junction Temperature | T_J | 225 | $^{\circ}\text{C}$ |
| Storage Temperature Range | T_{STG} | -65 to +150 | $^{\circ}\text{C}$ |





Thermal Characteristics

| Characteristic | Symbol | Value | Unit |
|--|-----------------|-------|----------------------|
| Thermal Resistance ($T_{CASE} = 70^{\circ}\text{C}, 50\text{ W CW}$) | $R_{\theta JC}$ | 0.58 | $^{\circ}\text{C/W}$ |

Ordering Information



| Type and Version | Order Code | Package | Shipping |
|--------------------|--------------------|--------------|----------------------|
| PXFE211507FC V1 R0 | PXFE211507FC-V1-R0 | H-37248G-4/2 | Tape & Reel, 50 pcs |
| PXFE211507FC V1 R2 | PXFE211507FC-V1-R2 | H-37248G-4/2 | Tape & Reel, 250 pcs |

Typical Performance (data taken in test fixture)





Typical Performance (data taken in test fixture)




Load Pull Performance

Load Pull Performance – Pulsed CW signal: 16 μs , 10% duty cycle, 28 V, $I_{DQ} = 900 \text{ mA}$

| | | P_{1dB} | | | | | | | | | |
|-------------------|---------------|-----------------------------|------------------|-----------------------------------|---------------------------------|--------------------------------|-----------------------------|------------------|-----------------------------------|---------------------------------|--------------------------------|
| | | Max Output Power | | | | | Max Drain Efficiency | | | | |
| Freq [MHz] | Zs [W] | ZL [W] | Gain [dB] | P_{1dB} [dBm] | P_{1dB} [W] | η_D [%] | ZL [W] | Gain [dB] | P_{1dB} [dBm] | P_{1dB} [W] | η_D [%] |
| 2110 | 3.3-j5.6 | 1.6-j3.5 | 18.6 | 52.75 | 188.4 | 52.7 | 3-j2 | 21.2 | 51.46 | 140 | 66.2 |
| 2170 | 5.1-j5 | 1.5-j3.9 | 18.3 | 52.80 | 190.6 | 51.4 | 3.7-j2.3 | 21.2 | 50.78 | 119.7 | 66.8 |

| | | P_{3dB} | | | | | | | | | |
|-------------------|---------------|-----------------------------|------------------|-----------------------------------|---------------------------------|--------------------------------|-----------------------------|------------------|-----------------------------------|---------------------------------|--------------------------------|
| | | Max Output Power | | | | | Max Drain Efficiency | | | | |
| Freq [MHz] | Zs [W] | ZL [W] | Gain [dB] | P_{3dB} [dBm] | P_{3dB} [W] | η_D [%] | ZL [W] | Gain [dB] | P_{3dB} [dBm] | P_{3dB} [W] | η_D [%] |
| 2110 | 3.3-j5.6 | 1.8-j3.9 | 16.7 | 53.56 | 227 | 56.8 | 4.3-j1.33 | 19.9 | 50.76 | 119.1 | 68.0 |
| 2170 | 5.1-j5 | 1.65-j3.9 | 16.5 | 53.64 | 231.2 | 55.8 | 3.7-j2.3 | 19.2 | 51.56 | 143.2 | 68.2 |

Reference Circuit, 2110 – 2170 MHz



Reference circuit assembly diagram (not to scale)

Reference Circuit Assembly


| | |
|---|---|
| DUT | PXFE211507FC V1 |
| Test Fixture Part No. | LTN/PXFE211507FC-V1 |
| PCB | Rogers 4350, 0.508 mm [0.020"] thick, 2 oz. copper, $\epsilon_r = 3.66$, $f = 2110 - 2170$ MHz |
| Find Gerber files for this test fixture on the Wolfspeed Web site at www.wolfspeed.com/RF | |

Components Information

| Component | Description | Manufacturer | P/N |
|------------------------------------|-------------------------------|---------------------------------|-------------------|
| Input | | | |
| C101, C102 | Capacitor, 0.4 pF | ATC | ATC600F0R4AT250BT |
| C103, C104, C106 | Capacitor, 10 pF | ATC | ATC600F100JT250XT |
| C105, C107 | Capacitor, 50 V, 10 μ F | Taiyo Yuden | UMK325C7106MM-T |
| R101, R102 | Resistor, 10 ohms | Panasonic Electronic Components | ERJ-3GEYJ100V |
| Output | | | |
| C201 | Capacitor, 18 pF | ATC | ATC600F180JT250XT |
| C202 | Capacitor, 0.4 pF | ATC | ATC600F0R4BT250XT |
| C203, C204 | Capacitor, 0.6 pF | ATC | ATC600F0R6BT250XT |
| C205, C206, C207, C209, C210, C211 | Capacitor, 50 V, 10 μ F | Taiyo Yuden | UMK325C7106MM-T |
| C208, C212 | Capacitor, 100 V, 220 μ F | Panasonic Electronic Components | ECA-2AHG221 |




Pinout Diagram (top view)



Lead connections for PXFE211507FC

Package Outline Specifications





Revision History

| Revision | Date | Data Sheet Type | Page | Subjects (major changes since last revision) |
|----------|------------|-----------------|------|---|
| 01 | 2018-09-12 | Advance | All | Data Sheet reflects advance specification for product development |
| 02 | 2019-01-15 | Production | All | Data Sheet reflects released product specification |

For more information, please contact:

4600 Silicon Drive
 Durham, North Carolina, USA 27703
www.wolfspeed.com/RF

Sales Contact
RFSales@wolfspeed.com

RF Product Marketing Contact
RFMarketing@wolfspeed.com
 919.407.7816

Notes

Disclaimer

Specifications are subject to change without notice. Cree, Inc. believes the information contained within this data sheet to be accurate and reliable. However, no responsibility is assumed by Cree for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Cree. Cree makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. “Typical” parameters are the average values expected by Cree in large quantities and are provided for information purposes only. These values can and do vary in different applications and actual performance can vary over time. All operating parameters should be validated by customer’s technical experts for each application. Cree products are not designed, intended or authorized for use as components in applications intended for surgical implant into the body or to support or sustain life, in applications in which the failure of the Cree product could result in personal injury or death or in applications for planning, construction, maintenance or direct operation of a nuclear facility.